



AP - 534EK

Features

- ❖ Heavy duty steel safe body reinforced with steel bar all around front edges to offer you a high level of protection.
- ❖ Six 25mm diameter locking bolts are made of solid steel
- ❖ Quality UL certified SecuRam electronic safe lock mounted on hardened steel plate.
- ❖ Torque limiting clutch mechanism
- ❖ Secondary relocking system.
- ❖ Mechanical override (operates on ROSS six-lever pick resistant safe lock) for digital lock.
- ❖ Manager's lockup (lever lock mounted on hardened steel plate).
- ❖ All locks are mounted on hardened steel plate.
- ❖ Programmable administrator code, two manager codes and 28 user codes.
- ❖ Built in safeguards against tampering - if any incorrect code is keyed in more than three consecutive times, the safe will automatically stay locked.
- ❖ Programmable time delay up to 99 minutes.
- ❖ Dual Mode (two codes are required to open safe if needed)
- ❖ Metal keypad housing. Operates on one 9 volt battery.
- ❖ Backlit LCD screen - on screen programming and battery voltage monitor.
- ❖ Four 15mm holes are provided in back panel for fixing with bolts.
- ❖ Up to 245 key hooks can be placed to suit single small keys to large vehicle keys.
- ❖ Three removable key panels with each panel having up to 70 key hooks.
- ❖ Carry handle and folding stand on each removable key panel
- ❖ 245 re-usable key tags.
- ❖ 245 printed number labels for key hooks.



Entry Pad



Manager's Override Lock



Specifications

Model	Ext. Dimensions * H x W x D (mm)	Body Thickness	Door Thickness	Weight *	Capacity	RETAIL PRICE (inc GST)
AP - 534EK	530 x 370 x 290	3mm	10mm	48Kg	245 KEYS	

SECUGUARD safes are covered by a twelve month warranty excluding freight & travelling.

* Weights and dimensions are approximate.

The safe pictures shown on this brochure are for illustrative purpose only.

We reserve the right to alter specifications without notice or obligation

Keywatch Systems Qld
 Tel: 07 5526 2726 Mob: 0436315271 0409762040
 sales@ksq.com.au